

IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-5 (Canceled)

6. (Previously Presented) An image display apparatus comprising:

means for receiving a video stream representing a series of consecutive input images, with the series of consecutive input images comprising a first image and a second image; and

a display device for displaying a series of consecutive output images which are based on the series of consecutive input images, wherein the image display apparatus is arranged:

to split the consecutive input images into respective first parts and respective second parts; and

to display a first one of the output images comprising a first

block of pixels corresponding to the first part of the first input image and a second block of pixels corresponding to the second part of the second input image;

a motion estimation unit for estimating motion in the first parts;

processing means to calculate a time period during which a particular part of the first parts moves from a first predetermined location relative to the display device to a second predetermined location relative to the display device; and

a selector to select a further one of the first parts of a further input image on basis of the time period.

7. (Previously Presented) The image display apparatus as claimed in Claim 6, further comprising a second memory device for storing the further one of the first parts.

Claims 8-10 (Canceled)

11. (Previously Presented) A method of displaying a series of consecutive output images which are based on a series of

consecutive input images, with the series of consecutive input images comprising a first image and a second image, the method comprising the acts of:

splitting the consecutive input images into respective first parts and respective second parts;

displaying a first one of the output images comprising a first block of pixels corresponding to the first part of the first input image and a second block of pixels corresponding to the second part of the second input image;

estimating motion in the first parts;

calculating a time period during which a particular part of the first parts moves from a first predetermined location relative to the display device to a second predetermined location relative to the display device; and

selecting a further one of the first parts of a further input image on basis of the time period.

Claims 12-15 (Canceled)

16. (Previously Presented) A display apparatus comprising:

an input configured to receive input images having
corresponding first input parts and second input parts;

a display device configured to display output images having
said corresponding first input parts and output parts;

a motion estimation unit for estimating motion in said second
input parts of said input images;

a processor configured to calculate a time period during which
a particular part of said second input parts moves from a first
predetermined location relative to the display device to a second
predetermined location relative to the display device; and

a selector to select a further one of said second input parts
of a further input image on basis of the time period;

wherein a predetermined number of said output images have said
output parts corresponding to one second input part of said second
input parts so that said one second input part is constantly
displayed over said predetermined number of said output images.

Claims 17-19 (Canceled)

20. (Previously Presented) An image display apparatus

comprising:

means for receiving a video stream representing a series of consecutive input images, with the series of consecutive input images comprising a first image and a second image; and

a display device for displaying a series of consecutive output images which are based on the series of consecutive input images, wherein the image display apparatus is arranged:

to split the consecutive input images into respective first parts and respective second parts;

to display a first one of the output images comprising a first block of pixels corresponding to the first part of the first input image and a second block of pixels corresponding to the second part of the second input image;

a character analyzer designed to search for textual information in the first parts; and

a comparing unit for comparing parts of the textual information with a predetermined string of characters;

wherein the first part is constantly displayed on the display device for viewing by a viewer as a constant image while the second part is variably displayed on the display device for viewing by the

viewer as a varying image.

21. (Currently Amended) A display apparatus comprising:
an input configured to receive input images having
corresponding first input parts and second input parts;
a display device configured to display output images having
said corresponding first input parts and output parts; and
a memory for writing and reading said second input parts,
wherein a frequency of the writing is zero in one mode so that a
same stored second input part is read for ~~the~~ viewing by ~~the~~ a
viewer as ~~the~~ a constant image.